Ultra-Silent 125

Model DCA-125USI

100 kW (125 kVA) **Prime Rating**
110 kW (137 kVA) **Standby Rating**
60 Hertz

Generator Specifications	
Standby Output	110 kW (137kVA)
Prime Output	100 kW (125 kVA)
Voltage – 3 phase	208-240 / 416-480 Switchable
Voltage – 1 phase	120 / 240 Switchable
Voltage Regulation	± 0.5% (no load to full load)
Power Factor	0.8 (3ph) or 1.0 (1ph)
Frequency	60 Hz
Frequency Regulation	Isochronous (no load to full load)
Sound Level	65 dB(A) - Full load at 23 feet

Amperage	
Rated Voltage	**Maximum Amps**
208 - 240 Volt (3ph)	300 Amps *
416 - 480 Volt (3ph)	150 Amps *
240 / 120 Volt (1ph)	300 Amps *
Main Line Circuit Breaker	300 Amps
Over Current Relay Trip	150 Amps (protects all settings)

* Voltage and phase are selected by a lockable, 3-position, rotary switch.

Engine Specifications	
Engine Make / Model	Isuzu / 4HK1X
Emissions	EPA Tier 3 Certified
Design – 4 cycle	4 cylinder, water cooled, turbocharged, aftercooled
Displacement	5.193 L
Bore x Stroke (mm)	115 x 125
Gross Engine Output	170 hp (127 kW)
Engine Speed	1800 rpm
Oil capacity	6.1 gallons (23.4 liters)
Battery	12V 128Ah x 1

Fuel System	
Fuel Tank Capacity	169 gallons (640 liters)
Fuel Consumption	
At full load gph (lph)	7.3 (27.6)
At 3/4 load gph (lph)	5.7 (21.7)
At 1/2 load gph (lph)	4.0 (15.1)
At 1/4 load gph (lph)	2.4 (9.1)

Standard Features

■ **Heavy duty, 4-cycle, direct injection diesel engine** provides maximum reliability.
■ **Brushless alternator** reduces service and maintenance requirements and meets temperature rise standards for Class F insulation systems.
■ **Open delta alternator design** provides virtually unlimited excitation for maximum motor starting capability.
■ **Automatic voltage regulator** (AVR) provides precise regulation.
■ **Automatic safety shutdown system** monitors the engine oil pressure and water temperature. Warning lights indicate abnormal conditions.
■ **Automatic start / stop control** automatically starts the generator set during a commercial power failure when used in conjunction with a transfer switch.
■ **Complete power panel**. Fully covered; three-phase terminals and single phase receptacles allow fast and convenient hookup for most applications including temporary power boxes, tools and lighting equipment. All are NEMA standard.
■ **Voltage selector switch** allows easy to change voltages as your applications require.



Dry Weight = 5689 lbs.



LOS ANGELES 310 835-3161 Fax 310 518-3019
BAKERSFIELD 661 335-0300 Fax 661 335-0333
FONTANA 909 823-6505 Fax 909 823-6955
website: http://www.assocpower.com e-mail: sales@assocpower.com

2/2010