



Standard Features

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- E-Z lube axle
- Large toolbox compartment
- Curbside instrument panel
- Shutdown system and annunciation module
- Battery disconnect switch
- Idle warm-up switch
- Rocker type start switch
- Emergency stop button
- Protective shutdown switches
- Fuel/Water separator
- Three state air filters
- Pneumatic inlet valve
- AWF compressor fluid
- Durable powder coat finish
- Wide track
- Galvanneal sheet metal
- Recessed taillights
- Rear bumper

■ AF Option provides Instrument Quality Air

- Produce instrument quality air per ISO 8573.1:Class 1.7.1.
- Aftercooler and moisture separator.
- Primary and secondary filters remove particulate to 0.01 micron and aerosols to 0.01 ppm.

■ 0 to 100% Capacity Control - Automatic inlet valve and unloaded starting.

■ Engine is EPA Tier 3 and CARB (California Air Resources Board) compliant.

■ Air End Warranty – 2 year standard warranty. 5-year or 10,000-hour warranty when continuously serviced at the recommended intervals with Sullair AWF Compressor Fluid and filters.

■ Durable Powder Coat Finish

■ Quiet Operation - Meets US EPA sound requirements at 76 dBA @ 7 meters.

Compressor	
Actual Delivery	375 cfm (10.6 m ³ /min, 177 L/sec)
Rated Pressure	200 psig (13.8 bar)
Pressure Range-min/max	80 / 200 psig (5.5 / 13.8 bar)
Air Outlets	Two – ¾" NPT
Compressor Oil Capacity	7 gal (26.5 L)
Receiver Tank Volume	2.46 ft ³ (0.07 m ³)

Engine	
Engine	JD4045HF(T3)
Operating Speed	2200 rpm
Available Power	140 bhp (104 kW)
Displacement	275cu. in. (4.507 L)
Cooling System Cap.	4 gal. (15.1 L)
Engine Oil Capacity	9 qt. (8.5 L)
Fuel Tank Capacity	56 gal. (211.9 L)
Electrical Sys. Voltage	12 volts
Battery Rating - CCA	1100

Dimensions	
Wet weight - tandem axle	4,440 lbs. (2014 kg)
Dry weight - tandem axle	4,050 lbs. (1787 kg)
Length	156.1 in. (3.966 m)
Width	77.2 in. (1.960 m)
Height	74 in. (1980 mm)
Track Width	67.5 in. (1.715 m)
Max. Towing Speed	55 MPH (89 km/h)
Axle Rating	5000 lbs. (2268 kg)
Tire Size	H78 x 15ST (D)

Performance	
Fuel consumption 100% load	6.55 gal. (24.8 L)
Max. Operating Altitude	10,000 ft. (3,048 m)